# Dual Ethernet Expansion Card

The Dual Ethernet Expansion Card provides an additional Ethernet port for the S1000 Controller using any of its 3 expansion slots.

FEATURES

- 10/100 TCP/IP Ethernet port
- Supports redundancy for the S1000 to PACOM VIGIL CORE
- An additional 10/100 Ethernet port
- SSL/TLS encryption support
- Automatically detected by the S1000

Datasheet

www.pacom.com

TECHNICAL SPECIFICATIONS

Physical	
Dimensions	80mm x 56mm (3.1" x 2.2")
Packed weight	50g (1.8oz)
Environmental	
Operating temperature	-10°C (14°F) to 70°C (158°F) UL 294: -10°C (14°F) to 49°C (120.2°F)
Maximum humidity	5% (0°C or 32°F) to 95% (40°C or 104°F)
Electrical	
Power consumption	60mA at 12VDC UL 294: 140mA at 12VDC input with full load
Communication	
Protocols	VIGIL CORE TCP/IP using SSL security
Physical	10/100 full duplex

COMPLIANCE AND ACCREDITATION

RoHS, RCM, FCC, CE

ORDERING INFORMATION

PART NO.	TYPE CODE	DESCRIPTION
320 200 106	SE1-ETHER2-PCB	Dual Ethernet Expansion Card

For Technical Support, contact info@pacom.com or +61 2 8459 0613.